

CRYSTAL OSCILLATOR (SPXO)
OUTPUT : CMOS, TTL

SG-615 series

SG-531 / SG-51 series

- Frequency range : 1.025 MHz to 135 MHz
- Supply voltage : 3.3 V Typ. / 5.0 V Typ.
- Function : Output enable(OE) or Standby(\overline{ST})
- Pin compatible with full-size metal can. (SG-51 series)
- Pin compatible with half-size metal can. (SG-531 series)


Product Number (please contact us)

- SG-615 : Q33615xx2xxxx00
- SG-531 : Q32531xx2xxxx00
- SG-51 : Q32510xx2xxxx00



Actual size


Specifications (characteristics)

| Item | Symbol | Specifications | | Conditions / Remarks |
|------------------------------|-------------|--|------------------------------------|---|
| | | SG-615P SG-531P SG-51P | SG-615PTJ SG-531PTJ SG-51PTJ | |
| Output frequency range | f_o | 1.025 MHz to 26 MHz | 26.001 MHz to 66.667 MHz | Please contact us about available frequencies. |
| Supply voltage | V_{cc} | 5.0 V ± 0.5 V | | |
| Storage temperature | T_{stg} | -55 °C to +125 °C | | Storage as single product. |
| Operating temperature | T_{use} | -20 °C to +70 °C | | |
| Frequency tolerance | f_{tol} | B ¹ : $\pm 50 \times 10^{-6}$, C: $\pm 100 \times 10^{-6}$ | | -20 °C to +70 °C |
| Current consumption | I_{cc} | 23 mA Max. | 35 mA Max. | No load condition |
| Disable current | I_{dis} | 12 mA Max. | 28 mA Max. | OE=GND |
| Symmetry | SYM | 40 % to 60 % | — | CMOS load:50 % V_{cc} level |
| | | 40 % to 60 % | 45 % to 55 % | TTL load: 1.4 V level |
| Output voltage | V_{OH} | $V_{cc}-0.4$ V Min. | 2.4 V Min. | $I_{OH}=-400 \mu A$ |
| | V_{OL} | 0.4 V Max. | | $I_{OL}=16$ mA(P)/ 8 mA(PTJ) |
| Output load condition (TTL) | L_{TTL} | 10 TTL Max. | 5 TTL Max. | $L_{CMOS} \leq 15$ pF |
| Output load condition (CMOS) | L_{CMOS} | 50 pF Max. | — | |
| Input voltage | V_{IH} | 2.0 V Min. | 3.5 V Min. | $I_{IH}=1 \mu A$ Max. (OE= V_{cc}) |
| | V_{IL} | 0.8 V Max. | 1.5 V Max. | $I_{IL}=-100 \mu A$ Min. (OE=GND), PTJ: $I_{IL}=-500 \mu A$ Min.(OE=GND) |
| Rise time / Fall time | t_r / t_f | 8 ns Max. | — | CMOS load:20 % V_{cc} to 80 % V_{cc} level |
| | | 8 ns Max. | 5 ns Max. | TTL load:0.4 V to 2.4 V level |
| Start-up time | t_{str} | 4 ms Max. | 10 ms Max. | Time at minimum supply voltage to be 0 s |
| Frequency aging | f_{aging} | $\pm 5 \times 10^{-6}$ / year Max. | | +25 °C, $V_{cc}=5.0$ V, First year |

*1 "B" tolerance will be available up to 55 MHz.

Specifications (characteristics)

| Item | Symbol | Specifications | | | Conditions / Remarks |
|------------------------|-------------|---|------------------------|--------------------------|---|
| | | SG-615PCG SG-531PCG | SG-615SCG SG-531SCG | SG-615PCN | |
| Output frequency range | f_o | 1.500 MHz to 26.000 MHz | | 26.001 MHz to 66.667 MHz | Please contact us about available frequencies. |
| Supply voltage | V_{cc} | 2.7 V to 3.6 V | | | |
| Storage temperature | T_{stg} | -55 °C to +125 °C | | | Storage as single product. |
| Operating temperature | T_{use} | -40 °C to +85 °C | | | |
| Frequency tolerance | f_{tol} | B: $\pm 50 \times 10^{-6}$ C: $\pm 100 \times 10^{-6}$ M: $\pm 100 \times 10^{-6}$ | | | -20 °C to +70 °C -40 °C to +85 °C |
| Current consumption | I_{cc} | 12 mA Max. | | 20 mA Max. | No load condition |
| Disable current | I_{dis} | 10 mA Max. | — | 10 mA Max. | OE=GND (PCG,PCN) |
| Stand-by current | I_{std} | — | 50 μA Max. | — | \overline{ST} =GND (SCG) |
| Symmetry | SYM | 45 % to 55 % | | | 50 % V_{cc} level, $L_{CMOS}=\text{Max.}$ |
| | | $V_{cc}-0.4$ V Min. | | $V_{cc}-0.4$ V Min. | $I_{OH}=8$ mA |
| Output voltage | V_{OH} | $V_{cc}-0.4$ V Min. | | 0.4 V Max. | $I_{OL}=8$ mA |
| | V_{OL} | 0.4 V Max. | | 15 pF Max. | |
| Output load condition | L_{CMOS} | 25 pF Max. | | 70 % V_{cc} Min. | OE Terminal or \overline{ST} Terminal |
| Input voltage | V_{IH} | 70 % V_{cc} Min. | | 30 % V_{cc} Max. | |
| | V_{IL} | 20 % V_{cc} Max. | | 4 ns Max. | 20 % V_{cc} to 80 % V_{cc} level, $L_{CMOS} \leq \text{Max.}$ |
| Rise time / Fall time | t_r / t_f | 4 ns Max. | | | |
| Start-up time | t_{str} | 12 ms Max. | | 10 ms Max. | $t=0$ at 90% V_{cc} |
| Frequency aging | f_{aging} | $\pm 5 \times 10^{-6}$ / year Max. | | | +25 °C, $V_{cc}=3.3$ V, First year |

Specifications (characteristics)

| Item | Symbol | Specifications | | | Conditions / Remarks |
|------------------------------|------------------------------------|--|------------------------------------|--|---|
| | | SG-615PTW / STW SG-531PTW / STW | SG-615PHW / SHW SG-531PHW / SHW | SG-615PCW / SCW SG-531PCW / SCW | |
| Output frequency range | f _o | 55.001 MHz to 135.000 MHz | | 26.001 MHz to 135.000 MHz | Please contact us about available frequencies. |
| Supply voltage | V _{cc} | 5.0 V ±0.5 V | | 3.3 V ±0.3 V | |
| Storage temperature | T _{stg} | -55 °C to +125 °C | | | Storage as single product. |
| Operating temperature | T _{use} | -20 °C to +70 °C | | -40 °C to +85 °C | |
| Frequency tolerance | f _{tol} | B: ±50 × 10 ⁻⁶ , C: ±100 × 10 ⁻⁶ | | M: ±100 × 10 ⁻⁶ | -20 °C to +70 °C -40 °C to +85 °C |
| Current consumption | I _{cc} | 45 mA Max. | | 28 mA Max. | No load condition (Max. frequency range) |
| Disable current | I _{dis} | 30 mA Max. | | 16 mA Max. | OE=GND (PTW,PHW,PCW) |
| Stand-by current | I _{std} | 50 µA Max. | | | ST=GND (STW,SHW,SCW) |
| Symmetry | SYM | 40 % to 60 % | 40 % to 60 % | — | 50 % V _{cc} level, L _{CMOS} =Max. 1.4 V level, L _{CMOS} =Max. |
| Output voltage | V _{OH} V _{OL} | V _{cc} -0.4 V Min. 0.4 V Max. | | | I _{OH} =-16 mA (PTW,STW,PHW,SHW), -8 mA (PCW,SCW) I _{OL} = 16 mA (PTW,STW,PHW,SHW), 8 mA (PCW,SCW) |
| Output load condition (TTL) | L _{TTL} | 5 TTL Max. | — | — | f _o ≤ 90 MHz, Max.supply voltage |
| Output load condition (CMOS) | L _{CMOS} | 15 pF Max. | | | Max.frequency, Max.supply voltage |
| Input voltage | V _{IH} V _{IL} | 2.0 V Min. 0.8 V Max. | | 70 % V _{cc} Min. 20 % V _{cc} Max. | OE Terminal or ST Terminal |
| Rise time / Fall time | t _r / t _f | 4 ns Max. | — | 4 ns Max. | 20 % V _{cc} to 80 % V _{cc} level, L _{CMOS} ≤ Max. 0.4 V to 2.4 V level |
| Start-up time | t _{str} | 10 ms Max. | | | Time at minimum supply voltage to be 0 s |
| Frequency aging | f _{aging} | ±5 × 10 ⁻⁶ / year Max. | | | +25 °C, V _{cc} =5.0 V / 3.3 V, First year |

*2 "C" tolerance : f_o ≥66.667 MHz(PTW,STW,PHW,SHW)

Product Name SG-615 P C G 20.000000MHz C
(Standard form) ① ②③ ④ ⑤
①Model ②Function (P: Output enable, S:Standby)
③Supply voltage ④Frequency
⑤Frequency tolerance

| ③Supply voltage | |
|-----------------|------------|
| C | 3.3 V Typ. |
| T,H | 5.0 V Typ. |
| Blank | 5.0 V Typ. |

| ⑤Frequency tolerance | |
|----------------------|--|
| B | ±50 × 10 ⁻⁶ / -20 to +70°C |
| C | ±100 × 10 ⁻⁶ / -20 to +70°C |
| M | ±100 × 10 ⁻⁶ / -40 to +85°C |


External dimensions

(Unit:mm)


Footprint (Recommended)

(Unit:mm)


● SG-615 series




● SG-615 series



● SG-531 series



● SG-51 series



Note.
OE pin (P,PTJ,PTW,PHW,PCW,PCN,PCG)
OE pin = "H" or "open" : Specified frequency output.
OE pin = "L" : Output is high impedance.

ST pin (STW, SHW, SCW,SCG)
ST pin = "H" or "open" : Specified frequency output.
ST pin = "L" : Output is low level
(weak pull - down), oscillation stops.

To maintain stable operation, provide a 0.01µF to 0.1µF by-pass capacitor at a location as near as possible to the power source terminal of the crystal product (between V_{cc} - GND).

PROMOTION OF ENVIRONMENTAL MANAGEMENT SYSTEM CONFORMING TO INTERNATIONAL STANDARDS

At Seiko Epson, all environmental initiatives operate under the Plan-Do-Check-Action (PDCA) cycle designed to achieve continuous improvements. The environmental management system (EMS) operates under the ISO 14001 environmental management standard.

All of our major manufacturing and non-manufacturing sites, in Japan and overseas, completed the acquisition of ISO 14001 certification.

ISO 14000 is an international standard for environmental management that was established by the International Standards Organization in 1996 against the background of growing concern regarding global warming, destruction of the ozone layer, and global deforestation.





WORKING FOR HIGH QUALITY

In order provide high quality and reliable products and services than meet customer needs,

Seiko Epson made early efforts towards obtaining ISO9000 series certification and has acquired ISO9001 for all business establishments in Japan and abroad. We have also acquired ISO/TS 16949 certification that is requested strongly by major automotive manufacturers as standard.

ISO/TS 16949 is the international standard that added the sector-specific supplemental requirements for automotive industry based on ISO9001.

► Explanation of the mark that are using it for the catalog

| | |
|---|---|
|  | ► Pb free. |
|  | ► Complies with EU RoHS directive. *About the products without the Pb-free mark. Contains Pb in products exempted by EU RoHS directive. (Contains Pb in sealing glass, high melting temperature type solder or other.) |
|  | ► Designed for automotive applications such as Car Multimedia, Body Electronics, Remote Keyless Entry etc. |
|  | ► Designed for automotive applications related to driving safety (Engine Control Unit, Air Bag, ESC etc.) |

Notice

- This material is subject to change without notice.
- Any part of this material may not be reproduced or duplicated in any form or any means without the written permission of Seiko Epson.
- The information about applied circuitry, software, usage, etc. written in this material is intended for reference only. Seiko Epson does not assume any liability for the occurrence of infringing on any patent or copyright of a third party. This material does not authorize the licensing for any patent or intellectual copyrights.
- When exporting the products or technology described in this material, you should comply with the applicable export control laws and regulations and follow the procedures required by such laws and regulations.
- You are requested not to use the products (and any technical information furnished, if any) for the development and/or manufacture of weapon of mass destruction or for other military purposes. You are also requested that you would not make the products available to any third party who may use the products for such prohibited purposes.
- These products are intended for general use in electronic equipment. When using them in specific applications that require extremely high reliability, such as the applications stated below, you must obtain permission from Seiko Epson in advance.
/ Space equipment (artificial satellites, rockets, etc.) / Transportation vehicles and related (automobiles, aircraft, trains, vessels, etc.) / Medical instruments to sustain life / Submarine transmitters / Power stations and related / Fire work equipment and security equipment / traffic control equipment / and others requiring equivalent reliability.
- All brands or product names mentioned herein are trademarks and/or registered trademarks of their respective.