

CRYSTAL OSCILLATOR (SPXO)

OUTPUT : LV-PECL, LVDS



Product Number
 SG3225EAN: X1G004251xxxx00
 SG3225VAN: X1G004241xxxx00
 SG5032EAN: X1G004271xxxx00
 SG5032VAN: X1G004261xxxx00
 SG7050EAN: X1G004291xxxx00
 SG7050VAN: X1G004281xxxx00

SG3225EAN / VAN
 SG5032EAN / VAN
 SG7050EAN / VAN

- Achieved wide frequency range by PLL technology and Fundamental AT crystal units
- Frequency range : 73.5 MHz to 700 MHz
- Supply voltage : 2.5 V to 3.3 V
- Function : Output enable (OE)
- Output : LV-PECL or LVDS



Specifications (characteristics)

Item	Symbol	Specifications		Conditions / Remarks
		LV-PECL SG3225EAN / SG5032EAN / SG7050EAN	LVDS SG3225VAN / SG5032VAN / SG7050VAN	
Output frequency range	f _o	73.5 MHz to 700 MHz		Please contact us about available frequencies.
Supply voltage	V _{cc}	K: 2.5 V - 10 % to 3.3 V + 10 %		
Storage temperature	T _{stg}	-40 °C to +125 °C		Storage as single product.
Operating temperature range	T _{use}	B: -20 °C to +70 °C, G: -40 °C to +85 °C		
Frequency tolerance range	f _{tol}	J: ± 50 × 10 ⁻⁶ , E: ± 30 × 10 ⁻⁶ , C: ± 20 × 10 ⁻⁶		
Current consumption	I _{cc}	65 mA Max.	30 mA Max.	OE = V _{cc} , L ECL = 50 Ω or L LVDS = 100 Ω
Disable current	I _{dis}	20 mA Max.		OE = GND
Symmetry	SYM	45 % to 55 %		At outputs crossing point
Output voltage (LV-PECL)	V _{OH}	V _{cc} - 1.0 V to V _{cc} - 0.8 V	-	DC characteristics
	V _{OL}	V _{cc} - 1.78 V to V _{cc} - 1.62 V	-	
Output voltage (LVDS)	V _{OD}	-	250 mV to 450 mV	DC characteristics
	dV _{OD}	-	50 mV Max.	
	V _{OS}	-	1.15 V to 1.35 V	
	dV _{OS}	-	150 mV Max.	
Output load condition (ECL) / (LVDS)	L _{ECL}	50 Ω	-	Terminated to V _{cc} -2.0 V
	L _{LVDS}	-	100 Ω	Connected between OUT to OUT
Input voltage	V _{IH}	70 % V _{cc} Min.		OE terminal
	V _{IL}	30 % V _{cc} Max.		
Rise time / Fall time	t _r / t _f	350 ps Max.	300 ps Max.	LV-PECL: Between 20 % and 80 % of (VOH-VOL). LVDS: Between 20 % and 80 % of Differential Output peak to peak voltage
Start-up time	t _{str}	3 ms Max.		Time at minimum supply voltage to be 0 s
Phase Jitter	t _{pj}	0.6 ps Max.*1		Offset frequency: 12 kHz to 20 MHz
Frequency aging	f _{age}	± 5 × 10 ⁻⁶ / year Max.		+25 °C, First year, V _{cc} = 2.5 V, 3.3 V

*1 0.9 ps Max. (f_o = 243 MHz ~ 250 MHz, 486 MHz ~ 500 MHz)

Product Name **SG3225 E AN 156.250000MHZ K J G A** (⑤⑥: CG is not available)
 (Standard form) ① ② ③ ④⑤⑥⑦
 ① Model ② Output (E: LV-PECL, V: LVDS) ③ Frequency ④ Supply voltage ⑤ Frequency tolerance
 ⑥ Operating temperature ⑦ Internal identification code ("A" is default)

④ Supply voltage		⑤ Frequency tolerance		⑥ Operating temperature	
K	2.5 V ~ 3.3 V	J	±50 × 10 ⁻⁶	B	-20 °C ~ +70 °C
E	±30 × 10 ⁻⁶	E	±30 × 10 ⁻⁶	G	-40 °C ~ +85 °C
C	±20 × 10 ⁻⁶	C	±20 × 10 ⁻⁶		

External dimensions (Unit: mm)

Footprint (Recommended) (Unit: mm)

