VOLTAGE-CONTROLLED CRYSTAL OSCILLATOR (VCXO)

Pb Free RoHS Compliant

Product Number
VG5032EDN: X1G004911xxxxxx
VG5032VDN: X1G004951xxxxxx

VG5032EDN
VG5032VDN

- Frequency range : 85 MHz to 170 MHz
- Supply voltage : 3.3 V
- Absolute pull range : 50 × 10^{-6} Min.
- External dimensions : 5.0 × 3.2 × 1.3 t (mm) Typ.
- Operation temperature : +85 C / +105 °C
- Function : Output Enable(OE), Active High
- Output : LV-PECL or LVDS

Specifications (characteristics)

Item	Symbol	LV-PECL VG5032EDN	LVDS VG5032VDN	Conditions / Remarks
Output frequency range	fo	85 MHz to 170 MHz		Please contact us for inquiries regarding available frequencies.
Supply voltage	V_{CC}	3.3 V ± 0.165 V		
Storage temperature	T_stg	-55 C to +125 C		Store as bare product.
Operating temperature	T_use	G: -40 C to +85 C, H: -40 C to +105 C		
Frequency tolerance	f_tol	±50 × 10^{-6} Max.		Includes initial tolerance, temperature change, V_{CC} change and 10years aging at +25 C. At V_C=1.65V, reference to f0
Absolute Pull range *1	APR	±50 × 10^{-6} Min.		V_C = 0 V to 3.3 V reference to f0
Input resistance	Rin	10 MΩ Min.		DC level
Current consumption	I_{CC}	60 mA Max.	30 mA Max.	OE = V_{CC}, LVPECL: 50 Ω, LVDS: 100 Ω
Symmetry	SYM	45 % to 55 %		LV-PECL: at V_{CC} - 1.30 V, V_C = 1/2V_{CC} LVDS: at outputs crossing point
Output voltage	V_{OH}	V_{CC} - 1.1 V Min.	–	LV-PECL: DC characteristics
	V_{OL}	V_{CC} - 1.5 V Max.	–	
	V_{OD}	–	250 mV to 450mV	V_{OD1}, V_{OD2} LVDS: DC characteristics
	V_{OS}	–	1.15 V to 1.35 V	V_{OS1}, V_{OS2}
Output load condition	L_ECL	50 Ω	–	LV-PECL: Terminated to V_{CC} - 2.0 V
	L_LVDS	–	100 Ω	LVDS: Connected between OUT to $\overline{OUT}$
Input voltage	V_{IH}	70 % V_{CC} Min.		OE terminal
	V_{IL}	30 % V_{CC} Max.		
Rise time / Fall time	tr / tf	0.5 ns Max.		LV-PECL: at 20 % to 80 % output swing
		0.3 ns Max.		LVDS: at 20 % and 80 % of Differential Output peek to peek voltage
Start-up time	t_str	10 ms Max.		Time at minimum supply voltage to be 0 s
Phase Jitter	t_{PJ}	0.3 ps Max.		Offset Frequency 12 kHz to 20 MHz

*1 Absolute pull range = Frequency control range- Frequency tolerance
* Please keep Vc pin open or ground while powering up V_{CC}.

Product name (Standard form)

VG5032 EDN 122.880000 MHz C J G H B A
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

①Model ②Output (E: LV-PECL, V: LVDS) ③Frequency ④Supply voltage (C: 3.3 V Typ)
⑤Frequency tolerance (J: ±50 × 10^{-6} Max.) ⑥Operating temperature (G: -40 to +85°C, H: -40 to +105°C)
⑦OE Function (H: Active High) ⑧Absolute Pull Range (B: ±50 × 10^{-6} Min.) ⑨Output Standby Type (A: High-Z)

External dimensions (Unit:mm)



Pin map

Pin	Connection
1	Vc
2	OE
3	GND
4	OUT1(positive)
5	OUT2(Negative)
6	Vcc

OE pin = "H" or "open" : Specified frequency output.
OE pin = "L": Output is high impedance.

Footprint (Recommended) (Unit:mm)



In order to achieve optimum jitter performance, it is recommended that the capacitor (0.1 µF + 10 µF) between V_{CC} and GND pin should be placed as close to the V_{CC} pin as possible.

►Explanation of the mark that are using it for the catalog

	►Pb free.
	►Complies with EU RoHS directive. *About the products without the Pb-free mark. Contains Pb in products exempted by EU RoHS directive. (Contains Pb in sealing glass, high melting temperature type solder or other.)
	►Designed for automotive general equipment.
	►Designed for automotive applications related to driving and safety.

NOTICE：PLEASE READ CAREFULLY BELOW BEFORE THE USE OF THIS DOCUMENT

1. The content of this document is subject to change without notice. Before purchasing or using Epson products, please contact with sales representative of Seiko Epson Corporation (“Epson”) for the latest information and be always sure to check the latest information published on Epson’s official web sites and resources.
2. This document may not be copied, reproduced, or used for any other purposes, in whole or in part, without Epson’s prior consent.
3. Information provided in this document including, but not limited to application circuits, programs and usage, is for reference purpose only. Epson makes no guarantees against any infringements or damages to any third parties’ intellectual property rights or any other rights resulting from the information. This document does not grant you any licenses, any intellectual property rights or any other rights with respect to Epson products owned by Epson or any third parties.
4. Epson has prepared this document carefully to be accurate and dependable, but Epson does not guarantee that the information is always accurate and complete. Epson assumes no responsibility for any damages you incurred due to any misinformation in this document.
5. Epson products listed in this document and our associated technologies shall not be used in any equipment or systems that laws and regulations in Japan or any other countries prohibit to manufacture, use or sell. Furthermore, Epson products and our associated technologies shall not be used for the purposes of military weapons development (e.g. mass destruction weapons), military use, or any other military applications. If exporting Epson products or our associated technologies, please be sure to comply with the Foreign Exchange and Foreign Trade Control Act in Japan, Export Administration Regulations in the U.S.A (EAR) and other export-related laws and regulations in Japan and any other countries and to follow their required procedures.
6. Epson assumes no responsibility for any damages (whether direct or indirect) caused by or in relation with your non-compliance with the terms and conditions in this document or for any damages (whether direct or indirect) incurred by any third party that you give, transfer or assign Epson products.
7. For more details or other concerns about this document, please contact our sales representative.
8. Company names and product names listed in this document are trademarks or registered trademarks of their respective companies.

●Disclaimer

1. Epson products are designed for use in general electronic equipment applications that do not require extremely high reliability or safety.

2. Epson does not represent or warrant that its products will not cause a failure for any particular application, except for cases where the failure is a direct result caused by defects in materials and workmanship of this product.
If a product fails due to defects in materials and workmanship, to the maximum extent permitted by law, we will, at our sole discretion, refund or replace the affected product.

3. When products for used directly or indirectly in certain devices or applications (ex. Nuclear power, aerospace, infrastructure facilities, medical equipment, etc.) which are connected to or affect safety of human life or property, Customer is solely responsible for determining if the products and respective specifications are suitable for the intended use in particular customer applications.
Customer shall implement necessary and proper safety design and measures (including redundant design, malfunction prevention design, etc.) to ensure reliability and safety before using the products in/with customer’s Equipment.

4.For the products designed for automotive applications, the products comply with AEC-Q100 or AEC-Q200.
Products do not comply with ISO 26262 (Products are not categorized to ASIL A, B, C and D).

5. No dismantling, analysis, reverse engineering, modification, alteration, adaptation, reproduction, etc., of Epson products is allowed.
Furthermore, any defects caused by this are not covered by the warranty.

©Seiko Epson Corporation 2025